

# UNGER®

# HYDRO POWER® RO SYSTEM

**EASY AND SAFE USAGE**



**BOOST MODE!**



**HIGH QUALITY 3-STAGE FILTRATION**

**POWERFUL HIGH-VALUE PUMP**



Scan here for more information



	HydroPower® RO
Part No.	R020S
Water output up to*	Boost mode: Up to 108 gal./h (409 l/h) Pure Water mode: Up to 60 gal./h (227 l/h)
Water outlets	1
Pump performance	0.50 HP
Electrical Specifications	Connection: 110V / 60Hz Consumption: 0.37 kW Min. Voltage: 104V / 60Hz
Protection class	Electric motor: IP 44 Pump Control: IP 65
Inlet pressure	14-87 PSI (1-6 Bar)
Max. operating pressure	145 PSI (10 Bar)
Pump dry run protection	✓
Water flow meter	Analog
Pre-filter	Combi filter Chlorine/Sediments (ROCFC)
Membrane	Membrane Unit (ROMEM) Maintenance Liquid (ROMML)
Resin filter	Resin Cartridge (RORFC)
TDS sensors	At water outlet
Compact Design	38" L × 21" W × 18" H
Tare weight	99 lbs.
Weight incl. filling	110 lbs.
Power Cord Length	20' / 6m

\*Flow rate will vary depending on factors such as water temp, PSI level, accessories used.

